



Trimble TDC150

HANDHELD

KEY FEATURES

- ▶ Integrated high-accuracy GNSS receiver
- ▶ Scalable positioning accuracy from meter to centimeters
- ▶ Android™ 6.0 operating system
- ▶ 5.3-inch sunlight readable multi-touch capacitive screen
- ▶ Google Mobile™ services certified to run Google core applications and services
- ▶ Compatible with Trimble or third-party software applications
- ▶ High speed 4G LTE cellular data connectivity
- ▶ Ultra-rugged design with MIL-STD-810 certification and rated IP67
- ▶ Removable, all day battery
- ▶ Fast Qualcomm® processor with 2 GB RAM and 16 GB internal storage
- ▶ Ergonomic form factor
- ▶ Front- and rear-facing cameras

Learn more:
geospatial.trimble.com/tdc150



Trimble TDC150 HANDHELD

GNSS CHARACTERISTICS

- 240 GNSS channels
 - GPS L1C/A, L1P(Y), L2P(Y), L2C
 - GLONASS L1C/A, L2C/A
 - BeiDou B1 (phase 2), B2
 - Galileo E1, E5b
 - QZSS L1C/A, L2C, L1SAIF
 - SBAS L1C/A
 - L-band
- Scalable accuracy from meter to centimeter (meter, sub meter (30/30), decimeter (7/2), centimeter)
- Patented Z-Blade technology for optimal GNSS performance
 - Full utilization of signals from all 6 GNSS systems (GPS, GLONASS, BeiDou, Galileo, QZSS and SBAS)
 - Enhanced GNSS-centric algorithm: fully-independent GNSS signal tracking and optimal data processing, including GPS-only, GLONASS-only or BeiDou-only solution (autonomous to full RTK)
 - Fast Search engine for quick acquisition and re-acquisition of GNSS signals
- Scalable SBAS ranging for using SBAS code & carrier observations and orbits in RTK Processing
- Patented Strobe™ Correlator for reduced GNSS multi-path
- Supported data formats: ATOM, CMR, CMR+, RTCM 2.1, 2.3, 3.0, 3.1 and 3.2 (including MSM), CMRx and sCMRx

REAL-TIME ACCURACY (RMS)¹⁻²

SBAS (WAAS/EGNOS/MSAS/GAGAN)

Horizontal < 50 cm
 Vertical < 85 cm

Real-Time DGPS position

Horizontal25 cm + 1 ppm
 Vertical50 cm + 1 ppm

Real-Time Kinematic Position (RTK)³

Horizontal 10 mm + 1 ppm
 Vertical 15 mm + 1 ppm

REAL-TIME PERFORMANCE

Instant-RTK⁴ Initialization Typically 2 sec for baselines < 20 km
 Up to 99.9% reliability
 over 40 km

RTK initialization range over 40 km

DATA LOGGING CHARACTERISTICS

Recording interval 1–999 seconds

PROCESSOR

- Qualcomm Snapdragon™ 410
- Quad-core
- Clock frequency: 1.2 GHz

OPERATING SYSTEM

- Android 6.0 (Google certified)
- Languages available: Afrikaans, German, English, Spanish, French, Italian, Portuguese (Portugal and Brazil), Japanese, Korean, Simplified Chinese, Greek, Russian, Azerbaijani, Czech, Danish, Lithuanian, Hungarian, Dutch, Norwegian (Bokmal), Romanian, Finnish, Swedish, Turkish, Bulgarian, Serbian (Cyrillic), Hindi, Polish
- Software package includes: Google Mobile Services

MEMORY

- 2 GB SDRAM
- Storage: 16 GB (non volatile).
- MicroSDHC™ memory card (up to 64 GB, SanDisk®, Kingston® recommended)

INTERFACE

- USB 2.0 (micro)
- External antenna connector (TNC)
- Audio jack 2.5 plug (CTIA/AHJ standards)

COMMUNICATIONS

- Cellular: GSM (850,900,1800,1900), GPRS, EDGE, UMTS, WCDMA (B1, B2, B5, B8), HSPA, TDSCDMA (B34, B39), LTE-FDD(B1, B3, B4, B5, B7, B8, B20), LTE-TDD (B38/B39/B40/B41)
- Wi-Fi (IEEE) 802.11 b/g/n
- Bluetooth® 4.0 dual mode
- USB (micro B USB connector)
- NFC

ENVIRONMENTAL CHARACTERISTICS

Operating temperature –20 °C to +60 °C (–4 °F to 140 °F)
 Storage temperature –30 °C to +70 °C without battery (–22 °F to 158 °F)⁵
 Humidity95% non condensing
 Water & dust proofIP67
 Free drop1.2 m on concrete
 ShocksMIL STD 810 (fig 516.5-10) (01/2000)
 VibrationMIL-STD-810F (fig 514.5C-17) (01/2000)

POWER CHARACTERISTICS

BatteryLi-Ion, 6400mAh
 Battery life> 8 hrs @ 20 °C with GNSS on
 Charging time4 hours
 Removable battery

PHYSICAL CHARACTERISTICS

Size29.5 x 12 x 4.5 cm (11.6 x 4.7 x 1.8 in)
 Weight850 g (1.87 lb)
 User interface2 volume keys, on/off/reset key, 2 programmable keys, standard Android touch panel buttons

On screen keyboard display

Size5.3" capacitive multi touch
 Resolution1280x720 pixels
 Brightness450 Cd/m²
 Gorilla Glass damage-resistant
 Auto rotatebetween Portrait and Landscape

MULTIMEDIA & SENSORS

- Rear camera 13 MP pixels with flash light
- Front camera 2 MP pixels
- E-Compass
- G-sensor
- Speaker
- Microphone
- Light sensor

STANDARD ACCESSORIES

- Handstrap
- Screen protectors (x2)
- A/C charger
- USB cable
- Pouch
- Battery door opener
- Monopole adaptor

OPTIONAL ACCESSORIES

- External GNSS antenna
- Pole bracket
- Monopole

OPERATING MODES

- RTK rover: Direct IP, NTRIP (VRS, FKP, MAC networks)
- Post-processing (if supported by the field application)

FIELD SOFTWARE

- Trimble TerraFlex™
- Trimble Penmap® for Android
- Third-party Android applications

1 Accuracy and TTFF specifications may be affected by atmospheric conditions, signal multipath, satellite geometry and corrections availability and quality.
 2 Performance values assume minimum of five satellites, following the procedures recommended in the product manual. High multipath areas, high PDOP values and periods of severe atmospheric conditions may degrade performance. Real time accuracies depend on TDC150 accuracy option.
 3 TDC150 centimeter used with Monopole accessory.
 4 Long baselines, long occupations, precise ephemeris used.
 5 Batteries can be stored up to +70 °C.
 6 Receiver convergence time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings. Convergence can be improved in RAM enabled regions.

Specifications are subject to change without notice.

Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA

Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE

Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC

Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE

